



Local Energy Advice Demonstrator (LEAD) project

Andy Gaisford

Senior Energy Project Officer
Surrey County Council

Agenda

- LEAD Background and Hypothesis
- SCC's LEAD project components
- LEAD stats to date
- Challenges and successes
- Broader Programme next steps
- Retrofit Guide and Supplementary Study
- LARA



Local Energy Advice Demonstrator (LEAD)

Project Hypothesis

IF via an innovative public-private-third sector partnership, we provide community-led, high quality **in-person energy advice**, incorporating home thermal imaging surveys; a **one-stop shop** for home energy improvements that enables residents to take the next tangible step; and a low-interest green home finance offer.

THEN we will generate stronger action among the ‘hard-to-reach consumers’ and ‘hard-to-treat properties’ audience segments in respect of energy efficiency improvements.

BECAUSE these audiences will be provided with streamlined and personalised support that breaks down barriers and blockers.



LEAD components




TBC...




LEAD components continued...




- ❖ Focus groups with key LEAD resident types
- ❖ HEAT Plus



[Facilitating Retrofit | UKGBC](#)



Timeline



LEAD Stats



£334,000

LEAD FUNDING
LEVERAGED



£85,000

MATCH FUNDING



5

PROJECT CHANGE
REQUESTS



924

HOUSEHOLDS
HELPED BY HEAT
AND HEAT PLUS




107

ENERGY
CHAMPIONS
TRAINED



72

FURBNOW HOME
ENERGY PLANS



6

HEAT → HEP
HOUSEHOLDS



10

RETROFIT
PROJECTS
COMMITTED



C. 200

HOUSEHOLDS W.
REMEDIAL
MEASURES



98%

'SATISFIED' OR
'VERY SATISFIED'
WITH HEAT



73%

'MORE LIKELY' TO
INSTALL
MEASURE(S)



5

FOCUS GROUPS
HOSTED



SURREY
COUNTY COUNCIL

Challenges

Project start delay

Spending the grant money

LEAD change control and reporting process

One-Stop Shop options

Green finance offer


Reaching (and helping) the hard to reach

Scams

Consumer knowledge

Intensity of advice provision

Broader programme next steps



Medium semi-detached house

This house type covers a wide range of different types of houses which may not look identical. Their size, construction age and condition will also be different and will have a significant impact on how much work might be needed and what measures are appropriate.

However, a variety of characteristics and constraints are common to semi-detached houses.

This guide aims to communicate clearly solutions likely to be suitable for one 'typical' version of a semi-detached house, a 'medium terraced house':

Do not worry if your house does not exactly fit into this description though. For example, you might live in a larger semi-detached house built in the 1950's. This guide will still be useful to you, but you will have to consider the advice with caution and consider it as a starting point. A building professional can help you identify specific recommendations for your house.

Built in 1900-1920

Approximate floor 120m²

Solid walls

Suspended floors

Presence of loft



Runnymede



Woking



Tadworth



Chertsey



Sunbury-on-Thames



Egham



Camberley



Ashford

Images taken from Google Street View ©Google 2024

Images taken from Google Street View ©Google 2024



Medium semi-detached house

Heat pump ready ✓

If your home is 'heat pump ready' it is likely you could install a heat pump without doing anything else. However, if you do not already have the features highlighted on this page, we recommend implementing them as they are cost effective and will improve your home, increase the performance of the heat pump and reduce your energy bills.



Solar panels

They work on south, east or west facing roofs and can significantly reduce your electricity bills.



Insulate loft

The loft is generally the easiest place to install insulation and can even be done as a DIY project. 300mm depth is best.



Install a heat pump and hot water cylinder

You will need a hot water cylinder inside and a heat pump unit outside. The back garden is likely to be the best option, but other locations may be possible too.



Improve ventilation

Fans extracting air from your kitchen and bathrooms will improve air quality in your home and reduce condensation.



Electricity supply

You will need to check your electricity supply is 80A – suitable for your heat pump installation.





Minimise draughts

Air leaks around the house (e.g. around windows and doors, through the chimney) waste a lot of energy (and money). Fixing them is possible and cost effective.



Savings



Estimated costs



Heat Pump
from £500* to £15,000

Solar Panels
from £3,000 to £9,000

Draughtproofing
from £300 to £500

Loft insulation
from £2,000 to £4,000

* Lower range assumes the contribution of funding and/or financing. Not all households will be eligible, see pages 41–42 for more information.

Supplementary housing retrofit study

Retrofit planning for affordable heat decarbonisation

The importance of heating load and flow temperature

When planning housing retrofits that are prioritised to deliver affordable decarbonisation of heat, two key technical considerations are the **peak heating load** and the **flow temperature for the heat emitters** (radiators).

Peak heating load

The peak heating load is the maximum instantaneous power output of the heating system that is expected to be required to maintain a comfortable internal temperature (18-21°C, depending on room type) at a minimum outdoor temperature. Heating load increases with dwelling size, air leakage of a building, and as insulation reduces. An accredited heat pump installer would be able to carry out a calculation to assess what is required for a typical house.


Most heat pumps can provide up to around 15kW of heat output on an 80A single phase supply, so if a dwelling's peak heat load exceeds this, fabric efficiency improvements are required to reduce peak heat load, or a potentially costly three phase electricity supply will be necessary to enable use of a more powerful heat pump.

Emitter flow temperature

Low flow temperatures are key to efficient heat pump operation and low running costs; however, the heat output of heat emitters reduces as flow temperature drops. This means that to use the low flow temperatures required to unlock the most efficient heat pump operation, either heat emitter sizes need to be increased to compensate, or a home's peak heat load needs to be reduced by improving the fabric efficiency (a combining both could be applied).

Dwelling size and fabric efficiency are indicators of peak load

The smaller the volume and more efficient a building's fabric, the lower the heating load. Heat pump installations in homes with lower heating loads will be simpler and less expensive than for large inefficient homes. There is a large range in the middle where minor fabric upgrades may be necessary or beneficial.



Relationship between peak heating load and emitter flow temperature. If a dwelling's peak heat load is above 15kW, it is likely that the heat load will need to be reduced, otherwise a 3-phase electrical supply may be required. Flow temperatures above 65°C usually mean that heat emitter upgrades are required to enable use of a heat pump, however ideally peak flow temperatures should be kept below 45°C for the best efficiencies.



SCC Housing retrofit study

Supplementary report in support of
The Surrey Home Energy Improvement Guide


September 2024



Supplementary housing retrofit study




Terraced houses in Surrey




Likelihood of a 'heat pump ready' housing stock (2/2)


Semi-detached houses in Surrey




Detached houses in Surrey




LARA Pilot Process; Overview



LARA Pilot Process; Understanding the System



LARA Pilot Process; Co-Design



Timeline

